

AMENDMENTS TO THE CLAIMS:

This listing of claims replaces all prior versions of claims in the application.

1-5. (Canceled)

6. (Currently amended) Method ~~according to claim 1~~for decreasing a transmission delay in a multi-sub-channel data transmission of physical layer frames using hybrid automated repeat request with acknowledgement signaling, further characterized bywherein said method comprises:

determining, if no physical layer frame needs to be transmitted in a provided sub-channel,

determining, if there is a physical layer frame of another sub-channel with pending acknowledgement,

selecting said physical layer frame with pending acknowledgement, if no physical layer frame needs to be transmitted in the provided sub-channel,

transmitting said selected frame in said provided sub-channel,

determining a threshold number, based on the number of sub-channels in said multi-sub-channel data transmission,

determining the number of physical layer frames to be transmitted in all sub-channels, and

controlling the transmission power of the transmission of the physical layer frames, on the basis of the relationship between said threshold number and said determined number of physical layer ~~frame~~frames.

7. (Original) Method according to claim 6, wherein said controlling of the transmission power comprises:

increasing the transmission power for the transmission of the physical layer frames, if said threshold number exceeds said determined number of physical layer frames to be transmitted.

8. (Previously presented) Method according to claim 6, further comprising determining an error rate, and wherein said determining of said threshold number, is also based on said determined error rate.

9. (Original) Method according to claim 8, wherein said controlling of said transmission power, is also related to said determined error rate.

10. (Previously presented) Method according to claim 6, wherein said controlling of the transmission power comprises:

decreasing the transmission power, if said determined number of physical layer frames to be transmitted exceeds said threshold number.

11-13. (Canceled)

14. (Previously presented) Wireless communication network device capable of decreased transmission delay in a multi-sub-channel data transmission of physical layer frames using hybrid automated repeat request with acknowledgement signaling, wherein said network device comprises:

a processing unit,
a storage, connected to said processing unit,
a radio interface for said multi-sub-channel data transmission of physical layer frames using hybrid automated repeat request, wherein said radio interface is connected to said processing unit and to said storage, and wherein said radio interface comprises a transmitter and a receiver,

a first component for determining, if no physical layer frame needs to be transmitted in a provided sub-channel,

a second component for determining, if there is a physical layer frame of another sub-channel with pending acknowledgement,

a third component for selecting, said physical layer frame with pending acknowledgement, if no physical layer frame needs to be transmitted in the provided sub-channel, and

a fourth component for transmitting said selected frame in said provided sub-channel,

wherein said first component said second component said third component and said fourth component are each connected to said radio interface, and wherein said first component is connected to said second component, said second component is connected to said third component, and said third component is connected to said fourth component.

15. (Previously presented) Wireless communication network device according to claim 14, further comprising:

a component for determining a threshold number, based on the number of sub-channels in said multi-sub-channel data transmission, wherein said component for determining said threshold number is connected to said radio interface;

a component for determining the number of physical layer frames to be transmitted in all sub-channels, wherein said component for determining said number of physical layer frames is connected to said radio interface, and

a component for controlling the transmission power of said transmitter for the transmission of the physical layer frames, in dependence of the relationship between said threshold number and said determined number of physical layer frames, wherein said component for controlling is connected to both of said components for determining and to said radio interface.

16. (Previously presented) Wireless communication network device according to claim 15,

wherein said network device is a mobile user terminal device.

17-22. (Canceled)

23. (Previously presented) Method according to claim 7, further comprising determining an error rate, and wherein said determining of said threshold number, is also based on said determined error rate.

24. (Previously presented) Method according to claim 9, wherein said controlling of the transmission power comprises decreasing the transmission power, if said determined number of physical layer frames to be transmitted exceeds said threshold number.

25. (Previously presented) Method according to claim 6, wherein said multi-sub-channel data transmission is an uplink of a dedicated transport channel in universal terrestrial radio access.

26. (Previously presented) Wireless communication network device according to claim 14, wherein said network device comprises a mobile user terminal device.

27. (New) A computer readable medium storing a computer program having instructions for executing a computer process, the process comprising:

- determining, if no physical layer frame needs to be transmitted in a provided sub-channel,

- determining, if there is a physical layer frame of another sub-channel with pending acknowledgement,

- selecting said physical layer frame with pending acknowledgement, if no physical layer frame needs to be transmitted in the provided sub-channel,

- transmitting said selected frame in said provided sub-channel,

determining a threshold number, based on the number of sub-channels in said multi-sub-channel data transmission,

determining the number of physical layer frames to be transmitted in all sub-channels, and

controlling the transmission power of the transmission of the physical layer frames, on the basis of the relationship between said threshold number and said determined number of physical layer frames.